



TESTING

1. Any Open, Short Miswiring & Intermittent are not permitted.
2. Contact Resistance: 5 Ω.
3. Insulation Resistance: 5MΩ/300V DC MIN.
4. This product is RoHS compliant.

PIN ASSIGNMENT

P1 DEUTSCH 9P M		P2 DEUTSCH 9P F		P3 Open
A	18AWG	A	24AWG	black
B	18AWG	B	24AWG	red
C	18AWG	C	24AWG	brown
D	18AWG	D	24AWG	orange
E	18AWG	E	24AWG	yellow
F	18AWG	F	24AWG	green
G	18AWG	G	24AWG	blue
H	18AWG	H	24AWG	purple
J	18AWG	J	24AWG	gray

Item	SPEC	QTY	UNIT
D	Cable: UL2464, 9C*24AWG+Al, OD=7.5mm, black jacket	1830	MM
C	Outer appearance molding: 45P PVC, black	1	PC
B	Deutsch Equivalent 9P Male connector: black core, inner insert & 9 terminals	1	PC
A	Deutsch Equivalent 9P Female connector: black core, red rubber seal, inner round ring & 9 terminals	1	SET

	Name	Deutsch 9Pin Angled M&F to DB15 M			
	Customer	Aftermarket			
DWG	YY Wang	Part No.	11760-03-235	Rev.	1.0
Check	Alex	Date	2015.07.14	N.W.	
Aprd	O. Acuña	Date	2015.07.14	Unit	MM